



AVESCO LIGHT COMPACTION EQUIPMENT – THE RIGHT FIT FOR YOUR JOBSITE

Technology and innovative design are the driving forces behind the durability, productivity and operator comfort built into every Avesco light compaction equipment.

www.avesco-cat.com

Avesco OÜ Estonia
Väljaotsa 1
76505 Saue
+372 679 9260
info.ee@avesco-cat.com

UAB Avesco Lithuania
Pirklių g. 6-101
Vilnius LT-02300
Tel. +370 5 2603242
info.lt@avesco-cat.com

**Contact
information:**
SIA Avesco Latvia
"Ziedu gravas"
Mārupes novads, LV-2167
Tel. +371 677 03513
info.lv@avesco-cat.com

**Work with confidence
and maximum precision**

 **avesco**



Forward moving vibratory plates: APF 12/40 and APF 20/50

High quality components make your avesco apf plate last bringing flexibility from one jobsite to the next .



Specifications APF 12/40

	Honda GX 120 engine:
Machine weight	69 kg
Base plate length	540 mm
Max. vibration frequency	98 Hz
Max. centrifugal force	12 kN
Surface capacity	480 m ² /hour
Compaction performance	15 cm

Specifications APF 20/50

	Honda GX 160 engine:	Hatz 1B20 engine:
Machine weight	88 kg	106 kg
Base plate length	559 mm	559 mm
Max. vibration frequency	90 Hz	90 HZ
Max. centrifugal force	20 kN	20 kN
Surface capacity	lki 1020 m ² /hour	lki 870 m ² /hour
Compaction performance	8,1 N/cm ²	15 N/cm ²

Reversible vibratory plates: APR 22/40 and APR 30/50

Comfortable handle is the key to avesco reversible vibratory plate success.



Specifications APR 22/40

	Hatz 1B20 engine:
Machine weight	118 kg
Base plate length	254 mm
Max. vibration frequency	98 HZ
Max. centrifugal force	23 kN
Surface capacity	528 m ² /hour
Spec. surface pressure	23,62 N/cm ²

Specifications APR 30/50

	Hatz 1B30 engine:
Machine weight	215 kg
Base plate length	330 mm
Max. vibration frequency	90 HZ
Max. centrifugal force	32 kN
Surface capacity	870 m ² /hour
Spec. surface pressure	23,62 N/cm ²

Premium Rammers: ATR 68 P

Avesco Premium rammers are technically advanced machines, adapted to help professionals be productive and safe.



	Honda GXR 120 engine:
Machine weight	68 kg
Foot length	340 mm
Foot width	280 mm
Percussion rate	680 bpm
Max. centrifugal force	13 kN
Surface capacity	225 m ² /hour
Max. compaction performance	50 cm



*Prices are excluding VAT. Offer is valid until until are available in the Avesco warehouse.

For more information about Avesco light compaction equipment, please contact our representatives or visit:
www.avesco-cat.com

